

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : EpoKwick FC Hardener  
Product code : 20-3453-032

#### 1.2. Recommended use and restrictions on use

Recommended use : Laboratory chemicals  
Restrictions on use : None known

#### 1.3. Supplier

Buehler  
41 Waukegan Rd  
Lake Bluff, IL 60044  
T 1-847-295-6500  
[custserv@buehler.com](mailto:custserv@buehler.com)

#### 1.4. Emergency telephone number

Emergency number : Global Access Code: 334545; Americas" +1 760 476 3962; Middle East/Africa: +1 760 476 3959;  
Asia Pacific +1 760 476 3960; Europe +1 760 476 3961

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Skin corrosion/irritation, Category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Respiratory sensitisation, Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.
Health hazard not otherwise classified, category 1		
Full text of H-statements: see section 16		

#### 2.2. GHS Label elements, including precautionary statements

##### GHS CA labelling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA) :

- H302 - Harmful if swallowed.
- H314 - Causes severe skin burns and eye damage.
- H317 - May cause an allergic skin reaction.
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 - May cause respiratory irritation.

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Precautionary statements (GHS CA) :

- P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P271 - Use only outdoors or in a well-ventilated area.
- P272 - Contaminated work clothing should not be allowed out of the workplace.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P284 - [In case of inadequate ventilation] wear respiratory protection.
- P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
- P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P302+P352 - IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 - Immediately call a POISON CENTER or doctor.
- P312 - Call a POISON CENTER or doctor if you feel unwell.
- P321 - Specific treatment (see supplemental first aid instruction on this label).
- P330 - Rinse mouth.
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
- P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
- P362+P364 - Take off contaminated clothing and wash it before reuse.
- P363 - Wash contaminated clothing before reuse.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
- P405 - Store locked up.
- P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	wt%	Classification (GHS CA)
1,2-Ethanediamine, N-(2-aminoethyl)-, polymer with oxirane	1,2-Ethanediamine, N1-(2-aminoethyl)-, polymer with oxirane	CAS-No.: 28063-82-3	> 70	Skin Corr. 1B, H314 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	wt%	Classification (GHS CA)
Diethylenetriamine	Bis(2-aminoethyl)amine / 2,2'-Diaminodiethylamine / Diethylamine, 2,2'-diamino- / Ethane-1,2-diamine, N-(2-aminoethyl)- / 1,2-Ethanediamine, N-(2-aminoethyl)- / Ethylenediamine, N-(2-aminoethyl)- / 2,2'-Iminobis(ethanamine) / 2,2'-Iminodi(ethylamine) / 1,4,7-Triazaheptane / N-(2-Aminoethyl)-1,2-ethanediamine / 1,2-Ethanediamine, N1-(2-aminoethyl)- / 3-Azapentane-1,5-diamine / DETA / N-(2-Aminoethyl)ethane-1,2-diamine / 2,2'-Iminobis(ethylamine) / 2,2'-Iminodiethylamine / Diethylene triamine	CAS-No.: 111-40-0	< 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 HHNOC 1

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	wt%	Classification (GHS CA)
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	Propylidynetrimethanol, propoxylated, reaction products with ammonia / Jeffamine T-403 / Polypropyleneglycol 2-aminopropyl ether, ether with 1,1,1-trimethylolpropane / Trimethylolpropane poly(oxypropylene)triamine / Polyetheramine T403 / MGE 914 / Tris(2-aminoethyl) ether of propoxylated trimethylolpropane	CAS-No.: 39423-51-3	5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
First-aid measures general	: Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Not determined.

#### 5.3. Specific hazards arising from the hazardous product

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Diethylenetriamine (111-40-0)

##### Canada (Alberta) - Occupational Exposure Limits

OEL TWA	4.2 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Diethylenetriamine (111-40-0)	
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWA)	4.2 mg/m <sup>3</sup>
VEMP (OEL TWA) [ppm]	1 ppm
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
Canada (Manitoba) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	4.2 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
Canada (Nova Scotia) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
OEL STEL [ppm]	2 ppm
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
OEL STEL [ppm]	2 ppm
Canada (Ontario) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
Canada (Prince Edward Island) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA [ppm]	1 ppm
OEL STEL [ppm]	2 ppm
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	4 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	4 mg/m <sup>3</sup>
OEL STEL [ppm]	1 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	1 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Colourless
Odour	: Amine-like
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 200 °C
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.03
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 10: Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

ATE CA (oral)	1666.667 mg/kg bodyweight
---------------	---------------------------

#### Diethylenetriamine (111-40-0)

LD50 oral rat	1080 mg/kg
LD50 dermal rabbit	672 mg/kg
LC50 Inhalation - Rat	70 mg/l/4h
ATE CA (oral)	500 mg/kg bodyweight
ATE CA (Dermal)	1100 mg/kg bodyweight

#### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (39423-51-3)

LD50 dermal rat	> 1000 mg/kg
ATE CA (oral)	500 mg/kg bodyweight
ATE CA (Dermal)	1100 mg/kg bodyweight

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause respiratory irritation.

#### 1,2-Ethanediamine, N-(2-aminoethyl)-, polymer with oxirane (28063-82-3)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.



# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.  
Hazardous to the aquatic environment, short-term (acute) : Not classified.  
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Diethylenetriamine (111-40-0)	
LC50 - Fish [1]	248 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
LC50 - Fish [2]	1014 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 - Crustacea [1]	16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	1164 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [1]	345.6 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [2]	592 mg/l (Species: Desmodesmus subspicatus)
BCF - Fish [1]	0.3 – 1.7
Partition coefficient n-octanol/water (Log Pow)	-1.3

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

Diethylenetriamine (111-40-0)	
BCF - Fish [1]	0.3 – 1.7
Partition coefficient n-octanol/water (Log Pow)	-1.3

#### 12.4. Mobility in soil

Diethylenetriamine (111-40-0)	
Partition coefficient n-octanol/water (Log Pow)	-1.3

#### 12.5. Other adverse effects

Ozone : Not classified.

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

#### 14.1. UN number

UN-No. (TDG) : UN1760

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT NA No : UN1760  
UN-No. (IMDG) : 1760  
UN-No. (IATA) : 1760


### 14.2. UN proper shipping name

Proper Shipping Name (TDG) : CORROSIVE LIQUID, N.O.S.  
Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.  
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S.  
Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.

### 14.3. Transport hazard class(es)

#### TDG

Transport hazard class(es) (TDG) : 8  
Hazard labels (TDG) : 8



#### DOT

Transport hazard class(es) (DOT) : 8  
Hazard labels (DOT) : 8



#### IMDG

Transport hazard class(es) (IMDG) : 8  
Danger labels (IMDG) : 8



#### IATA

Transport hazard class(es) (IATA) : 8  
Danger labels (IATA) : 8



### 14.4. Packing group

Packing group (TDG) : III  
Packing group (DOT) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III

### 14.5. Environmental hazards

Other information : No supplementary information available.

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 14.6. Special precautions for user

#### TDG

UN-No. (TDG)	: UN1760
TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L
Emergency Response Guide (ERG) Number	: 154

#### DOT

UN-No.(DOT)	: UN1760
DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

#### IMDG

Special provisions (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

### IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. National regulations

#### 1,2-Ethanediamine, N-(2-aminoethyl)-, polymer with oxirane (28063-82-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Diethylenetriamine (111-40-0)

Listed on the Canadian DSL (Domestic Substances List)

#### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (39423-51-3)

Listed on the Canadian DSL (Domestic Substances List)

### 15.2. International regulations

#### 1,2-Ethanediamine, N-(2-aminoethyl)-, polymer with oxirane (28063-82-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the Japanese ISHL (Industrial Safety and Health Law)

# EpoKwick FC Hardener

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### Diethylenetriamine (111-40-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Japanese Poisonous and Deleterious Substances Control Law  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the Japanese ISHL (Industrial Safety and Health Law)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (39423-51-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on ELINCS (European List of Notified Chemical Substances)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the Japanese ISHL (Industrial Safety and Health Law)

## SECTION 16: Other information

Issue date : 05/17/2022  
Revision date : 05/17/2022

### Full text of H-statements:

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS), Canada

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable