

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : SamplKwick Liquid
Product code : 20-3564, 20-3564-320, 20-3564-640, 20-3568

1.2. Recommended use and restrictions on use

Recommended use : Laboratory chemicals
Restrictions on use : None known

1.3. Supplier

Buehler
41 Waukegan Rd
Lake Bluff, IL 60044
T 1-847-295-6500
custserv@buehler.com

1.4. Emergency telephone number

Emergency number : Global Access Code: 334545; Americas" +1 760 476 3962; Middle East/Africa: +1 760 476 3959; Asia Pacific +1 760 476 3960; Europe +1 760 476 3961

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable liquids, Category 3	H226	Flammable liquid and vapour.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3,	H335	May cause respiratory irritation.
Respiratory tract irritation		

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA) :




Signal word (GHS CA) : Warning

Hazard statements (GHS CA) :

- H226 - Flammable liquid and vapour.
- H315 - Causes skin irritation.
- H317 - May cause an allergic skin reaction.
- H319 - Causes serious eye irritation.
- H335 - May cause respiratory irritation.

Precautionary statements (GHS CA) :

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 - Keep container tightly closed.

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	wt%	Classification (GHS CA)
Isobutyl methacrylate	2-Methylpropyl 2-methylprop-2-enoate / 2-Methylpropyl 2-methyl-2-propenoate / Isobutyl 2-methylprop-2-enoate / Isobutyl methacrylate, stabilized / 2-Propenoic acid, 2-methyl-, 2-methylpropyl ester / ISOBUTYL METHACRYLATE / 2-Methylpropyl methacrylate / Methacrylic acid, isobutyl ester / 2-Methyl-2-propenoic acid, 2-methylpropyl ester	CAS-No.: 97-86-9	< 90	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Not determined.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Colourless Yellow
Odour	: Acrid
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 155 °C
Flash point	: 46 °C
Auto-ignition temperature	: 390 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Relative density	: 0.913
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Isobutyl methacrylate (97-86-9)	
LD50 oral rat	9590 mg/kg
ATE CA (oral)	9590 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause respiratory irritation.

Isobutyl methacrylate (97-86-9)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
-------------------	---

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hazardous to the aquatic environment, short-term : Not classified.
(acute)

Hazardous to the aquatic environment, long-term : Not classified.
(chronic)

Isobutyl methacrylate (97-86-9)

LC50 - Fish [1]	20 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	0.29 mg/l (Species: Pseudokirchneriella subcapitata)
Partition coefficient n-octanol/water (Log Pow)	2.95 (at 20 °C (at pH 0))

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isobutyl methacrylate (97-86-9)

Partition coefficient n-octanol/water (Log Pow)	2.95 (at 20 °C (at pH 0))
---	---------------------------

12.4. Mobility in soil

Isobutyl methacrylate (97-86-9)

Partition coefficient n-octanol/water (Log Pow)	2.95 (at 20 °C (at pH 0))
---	---------------------------

12.5. Other adverse effects

Ozone : Not classified.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

14.1. UN number

UN-No. (TDG) : UN2283
DOT NA No : UN2283
UN-No. (IMDG) : 2283
UN-No. (IATA) : 2283

14.2. UN proper shipping name

Proper Shipping Name (TDG) : ISOBUTYL METHACRYLATE, STABILIZED
Proper Shipping Name (DOT) : Isobutyl methacrylate, stabilized
Proper Shipping Name (IMDG) : ISOBUTYL METHACRYLATE, STABILIZED
Proper Shipping Name (IATA) : Isobutyl methacrylate, stabilized

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 3

Hazard labels (TDG) : 3

:



DOT

Transport hazard class(es) (DOT) : 3

Hazard labels (DOT) : 3

:



IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3

:



IATA

Transport hazard class(es) (IATA) : 3

Danger labels (IATA) : 3

:



14.4. Packing group

Packing group (TDG) : III

Packing group (DOT) : III

Packing group (IMDG) : III

Packing group (IATA) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN2283

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

TDG Special Provisions	: 155 - (1) If these dangerous goods are stabilized by temperature control, they must be offered for transport, handled and transported in accordance with section 7.1.6 of the UN Recommendations. (2) If chemical stabilization is employed, the person offering the means of containment for transport must ensure that the level of stabilization will prevent a dangerous polymerization of the dangerous goods at a bulk mean temperature of 50°C in the case of a small means of containment or an intermediate bulk container (IBC) or, in the case of a large means of containment that is not an IBC, at a bulk mean temperature of 45°C. (3) If chemical stabilization may become ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In determining whether chemical stabilization may become ineffective at lower temperatures, the person offering the means of containment for transport must take at least the following factors into consideration: (a) the capacity and geometry of the means of containment and the effect of any insulation; (b) the temperature of the dangerous goods when offered for transport; (c) the duration of the transport and the seasonal ambient temperature conditions typically encountered during transport; and (d) the effectiveness and other physical or chemical properties of the stabilizer employed.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L
Emergency Response Guide (ERG) Number	: 130P
DOT	
UN-No.(DOT)	: UN2283
DOT Special Provisions (49 CFR 172.102)	: 387 - When materials are stabilized by temperature control, the provisions of §173.21(f) of this subchapter apply. When chemical stabilization is employed, the person offering the material for transport shall ensure that the level of stabilization is sufficient to prevent the material as packaged from dangerous polymerization at 50 °C (122 °F). If chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required and is forbidden by aircraft. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging and the effect of any insulation present, the temperature of the material when offered for transport, the duration of the journey, and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g.requirements to protect from sources of heat, including other cargo carried at a temperature above ambient) and any other relevant factors. The provisions of this special provision will be effective until January 2, 2019, unless we terminate them earlier or extend them beyond that date by notice of a final rule in the Federal Register. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (t_r - t_f))$ Where: t_r is the maximum mean bulk temperature during transport, and t_f is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat

IMDG

Special provisions (IMDG)	: 386
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: C
Flash point (IMDG)	: 49°C c.c.
Properties and observations (IMDG)	: Colourless liquid. Flashpoint: 49°C c.c. Immiscible with water. Irritating to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A209
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

Isobutyl methacrylate (97-86-9)

Listed on the Canadian DSL (Domestic Substances List)

SamplKwick Liquid

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Trimethylolpropane trimethacrylate (3290-92-4)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Isobutyl methacrylate (97-86-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Trimethylolpropane trimethacrylate (3290-92-4)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Issue date : 08/03/2022
Revision date : 08/03/2022

Full text of H-statements:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Safety Data Sheet (SDS), Canada

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable