

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product Name** VariDur 3003 Liquids 1 & 2

**Product Code(s)** 20-3532, 20-3535, 20-3536

**(M)SDS Number** 1346124\_A

### Other means of identification

**UN-No.** UN1866

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Laboratory Use Only

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

**Manufacturer** Buehler

**Manufacturer Address** 41 Waukegan Rd  
Lake Bluff, IL 60044  
www.buehler.com

**Phone number** +1 847 295 6500

**E-mail Address** custserv@buehler.com

### Emergency telephone number

Global Access Code: 334545

Americas: +1 760 476 3962

Middle East/Africa: +1 760 476 3959

Asia Pacific: +1 760 476 3960

Europe: +1 760 476 3961

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2

Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 2

**GHS Label elements, including precautionary statements****Emergency Overview**

<b>Signal word</b>	<b>Danger</b>	
<b>Hazard Statements</b>	<p>Causes skin irritation          Causes serious eye irritation          May cause an allergic skin reaction          Suspected of causing cancer          Suspected of damaging fertility or the unborn child          May cause respiratory irritation          Causes damage to organs through prolonged or repeated exposure          Highly flammable liquid and vapor</p>	
		
<b>Appearance</b>	No information available	<b>Physical state</b> Liquid
		<b>Odor</b> Characteristic

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Contaminated work clothing should not be allowed out of the workplace  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Keep cool

**Precautionary Statements - Response**

None

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

**Skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other information**

No information available

**Interactions with Other Chemicals**

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No	Weight-%	Trade Secret
Methyl methacrylate	80-62-6	10 - 50%	*
Styrene	100-42-5	2.5 - 50%	*
Benzenamine, N,N,4-trimethyl-	99-97-8	0 - 2.5%	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

**Skin contact**

May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

**Inhalation**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

**Ingestion**

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

**Self-protection of the first aider**

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** Burning sensation. Itching. Rashes. Hives. Coughing and/ or wheezing.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** May cause sensitization in susceptible persons. Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Water spray, fog or alcohol-resistant foam. Use water spray or fog; do not use straight streams. Dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray.

**Unsuitable extinguishing media**

CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

**Uniform Fire Code** Sensitizer: Liquid

**Explosion Data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** Yes.

**Protective equipment and precautions for firefighters**

Move containers from fire area if you can do it without risk.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.
<b>Other Information</b>	Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### Environmental precautions

<b>Environmental precautions</b>	Prevent entry into waterways, sewers, basements or confined areas.
----------------------------------	--

### Methods and material for containment and cleaning up

<b>Methods for containment</b>	A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
<b>Methods for cleaning up</b>	Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

<b>Handling</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.
-----------------	---

### Conditions for safe storage, including any incompatibilities

<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
<b>Incompatible Products</b>	Strong acids. Strong oxidizing agents. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

<b>Exposure Guidelines</b>	The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure
----------------------------	--

limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl methacrylate 80-62-6	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 410 mg/m <sup>3</sup>	IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>
Styrene 100-42-5	STEL: 40 ppm TWA: 20 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m <sup>3</sup> (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m <sup>3</sup> Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m <sup>3</sup> STEL: 100 ppm STEL: 425 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

### Appropriate engineering controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/face protection** If splashes are likely to occur. None required for consumer use. Tight sealing safety goggles.

**Skin and body protection** Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Characteristic
<b>Appearance</b>	No information available	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	<b>Method</b>
<b>pH</b>	Not determined		
<b>Melting / freezing point</b>	No data available	None known	
<b>Boiling point / boiling range</b>	101°C °C / 214 °F		
<b>Flash Point</b>	26°C C / 79 F		

<b>Evaporation Rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit</b>	No data available	
<b>Lower flammability limit</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Specific Gravity</b>	1.05	
<b>Water Solubility</b>	Immiscible	
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known
<b>Explosive properties</b>	No data available	
<b>Oxidizing properties</b>	No data available	

**Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	Not applicable
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong acids. Strong oxidizing agents. Strong bases.

**Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information****Inhalation**

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

**Eye contact**

Specific test data for the substance or mixture is not available. (based on components). May cause redness, itching, and pain. Causes serious eye irritation.

**Skin contact** Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### Component Information

Chemical name	LD50 Oral	LD50 Dermal	Inhalation LC50
Methyl methacrylate 80-62-6	= 7900 mg/kg ( Rat ) = 7872 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	= 4632 ppm ( Rat ) 4 h
Styrene 100-42-5	= 1000 mg/kg ( Rat )		= 11.7 mg/L ( Rat ) 4 h
Benzenamine, N,N,4-trimethyl- 99-97-8	= 1650 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	= 1400 mg/m <sup>3</sup> ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives. Coughing and/ or wheezing.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** May cause sensitization in susceptible persons. May cause sensitization by skin contact.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Methyl methacrylate 80-62-6		Group 3		
Styrene 100-42-5		Group 2B	Reasonably Anticipated	X
Benzenamine, N,N,4-trimethyl- 99-97-8		Group 2B		

*IARC (International Agency for Research on Cancer)*

*Group 2B - Possibly Carcinogenic to Humans*

*Group 3 - Not Classifiable as to Carcinogenicity in Humans*

*NTP (National Toxicology Program)*

*Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

**Reproductive toxicity** Contains a known or suspected reproductive toxin.

**STOT - single exposure** Respiratory system.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

**Chronic Toxicity** Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

**Target Organ Effects**

Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Reproductive system. Central nervous system (CNS). Liver. Blood.

**Aspiration Hazard**

No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl methacrylate 80-62-6	96h EC50: = 170 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 243 - 275 mg/L (Pimephales promelas) 96h LC50: 125.5 - 190.7 mg/L (Pimephales promelas) 96h LC50: 153.9 - 341.8 mg/L (Lepomis macrochirus) 96h LC50: > 79 mg/L (Oncorhynchus mykiss) 96h LC50: 170 - 206 mg/L (Lepomis macrochirus) 96h LC50: 326.4 - 426.9 mg/L (Poecilia reticulata)		48h EC50: = 69 mg/L
Styrene 100-42-5	96h EC50: = 0.72 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.15 - 3.2 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.46 - 4.3 mg/L (Pseudokirchneriella subcapitata) 72h EC50: = 1.4 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 3.24 - 4.99 mg/L (Pimephales promelas) 96h LC50: 6.75 - 14.5 mg/L (Pimephales promelas) 96h LC50: 58.75 - 95.32 mg/L (Poecilia reticulata) 96h LC50: 19.03 - 33.53 mg/L (Lepomis macrochirus)	EC50 = 5.4 mg/L 5 min	48h EC50: 3.3 - 7.4 mg/L
Benzenamine, N,N,4-trimethyl- 99-97-8		96h LC50: 42 - 50.5 mg/L (Pimephales promelas)		

### Persistence and Degradability

No information available.

### Bioaccumulation

Chemical name	Log Pow
Methyl methacrylate 80-62-6	0.7
Styrene 100-42-5	2.95
Benzenamine, N,N,4-trimethyl- 99-97-8	2.81

### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

<b>Disposal methods</b>	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Should not be released into the environment. Dispose of contents/containers in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
<b>Contaminated Packaging</b>	Dispose of contents/containers in accordance with local regulations.
<b>US EPA Waste Number</b>	D001 U162

### **California Hazardous Waste Codes** 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Methyl methacrylate 80-62-6	Toxic Ignitable
Styrene 100-42-5	Toxic Ignitable

## 14. TRANSPORT INFORMATION

### DOT

<b>UN-No.</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Reportable Quantity (RQ) (RQ/% in mixture)</b>	STYRENE MONOMER: RQ KG= 4540.00, METHYL METHACRYLATE: RQ KG= 1135.00
<b>Description</b>	UN1866, RESIN SOLUTION, 3, III, RQ
<b>Emergency Response Guide Number</b>	127

### TDG

<b>UN Number</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class (select)</b>	3
<b>Packing Group (select)</b>	III
<b>Description</b>	UN1866, RESIN SOLUTION, 3, III

### MEX

<b>UN-No.</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Description</b>	UN1866, RESIN SOLUTION, 3, III

### ICAO

<b>UN-No.</b>	UN1866
<b>Proper Shipping Name</b>	RESIN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Description</b>	UN1866, RESIN SOLUTION, 3, III

**IATA**

UN Number	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class (select)	3
Packing Group (select)	III
Description	UN1866, RESIN SOLUTION, 3, III

**IMDG**

UN Number	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class (select)	3
Packing Group (select)	III
EmS-No.	F-E, S-E
Description	UN1866, RESIN SOLUTION, 3, III, (26°C C.C.)

**RID**

UN-No.	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	III
Classification code	F1
Description	UN1866, RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS, 3, III
ADR/RID-Labels	3

**ADR**

UN-No.	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	III
Classification code	F1
Tunnel restriction code	(D/E)
Description	UN1866, RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS, 3, III, (D/E)

**ADN**

UN-No.	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3
Packing Group	III
Classification code	F1
Special Provisions	640E
Description	UN1866, RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS, 3, III
Hazard Labels	3
Limited Quantity	5 L
Ventilation	VE01

## 15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
IECSC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS-No	Weight-%	SARA 313 - Threshold Values %
Methyl methacrylate - 80-62-6	80-62-6	10 - 50%	1.0
Styrene - 100-42-5	100-42-5	2.5 - 50%	0.1

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Methyl methacrylate 80-62-6	1000 lb			X
Styrene 100-42-5	1000 lb			X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl methacrylate 80-62-6	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Styrene 100-42-5	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

#### US State Regulations

##### California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Styrene - 100-42-5	Carcinogen
Benzenamine, N,N,4-trimethyl- - 99-97-8	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Methyl methacrylate 80-62-6	X	X	X	X	X
Styrene 100-42-5	X	X	X	X	X

#### International Regulations

##### Mexico

##### National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Methyl methacrylate 80-62-6 ( 10 - 50% )		Mexico: TWA 100 ppm Mexico: TWA 410 mg/m <sup>3</sup> Mexico: STEL 125 ppm Mexico: STEL 510 mg/m <sup>3</sup>
Styrene		Mexico: TWA 50 ppm

100-42-5 ( 2.5 - 50% )		Mexico: TWA 215 mg/m <sup>3</sup> Mexico: STEL 100 ppm Mexico: STEL 425 mg/m <sup>3</sup>
------------------------	--	---

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada

#### WHMIS Hazard Class

Not determined

## 16. OTHER INFORMATION

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Physical and Chemical Hazards - Personal Protection</b> X
<b>HMS</b>	<b>Health Hazards</b> 2 *	<b>Flammability</b> 3	<b>Physical Hazard</b> 0	

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 01-Mar-2017  
**Revision Date** 12-Sep-2018  
**Revision Note** No information available

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

**End of Safety Data Sheet**